

**3 PLY RED SILICONE TS**

<b>BELT</b>	<b>FABCO BRITE w/ SILICONE</b>
<b>TYPE</b>	<b>FLAT SURFACE</b>
<b>COLOR</b>	<b>RED</b>
<b>PLIES</b>	<b>3</b>
<b>WEIGHT (LBS. SQ. FT.)</b>	<b>0.630</b>
<b>AVAILABLE WIDTH (INCHES)</b>	<b>72 STANDARD</b>
<b>OVERALL GAUGE (INCHES)</b>	<b>0.137 +/- 0.015</b>
<b>TENSILE STRENGTH (LBS./IN. OF WIDTH)</b>	<b>1200</b>
<b>RECOMMENDED WORKING TENSION (LBS./IN. OF WIDTH)</b>	<b>120</b>
<b>MINIMUM PULLEY DIAMETER (INCHES)</b>	<b>4</b>
<b>TEMPERATURE RANGE (°F)</b>	<b>0 TO 325</b>
<b>APPROVED FOR TOBACCO USE</b>	<b>MEETS AND/OR EXCEEDS REQUIREMENTS FOR DIRECT CONTACT WITH TOBACCO.</b>
<b>MEETS FDA REQUIREMENTS</b>	<b>YES</b>
<b>MAJOR POLYMER CONTENT</b>	<b>NATURAL RUBBER</b>
<b>COVER SURFACE CONFIGURATION</b>	<b>SILICONE</b>
<b>BOTTOM SURFACE CONFIGURATION</b>	<b>BARE STRIKE THRU</b>
<b>COEFFICIENT OF FRICTION</b>	<b><u>STEEL</u>    <u>CARDBOARD</u></b>
<b>COVER SURFACE</b>	<b>0.20    0.40</b>
<b>BOTTOM SURFACE</b>	<b>0.20    0.40</b>
<b>TYPICAL END-USE APPLICATION</b>	<b>CONVEYING TOBACCO PRODUCTS</b>

**GENERAL COMMENTS:**

**100% POLYESTER CARCASS, NO STRETCH, BETTER MOISTURE RESISTANCE, NON STAINING, GOOD RELEASE**

