



DERCOUSA

BELT SPECIFICATION
CONVEYOR BELTS

FPS20-04/AI (90 DUROMETER CLEAR POLYOLEFIN COVER WITH FRAYLESS FABRIC)

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	
TOP COVER	CLEAR
POLYOLIFINE	
TOP COVER THICKNESS	.02"
BOTTOM COVER	FABRIC IMPREGNATION
BOTTOM COVER THICKNESS	
BELT THICKNESS	.087"
WEIGHT PER SQ. FT.	.49 LBS/SQ. FT
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	YES
MAXIMUM WIDTH	2000 MM
WORKING STRENGTH @ 1% ELONGATION	57.1 LBS PER INCH
TEMPERATURE RANGE	-58 F TO 158 F
MINIMUM PULLEY DIAMETER	.98"
CO EFFICIENT OF FRICTION	
STEEL	.4
TYPE BELT SUPPORT	SLIDER BED ROLLER BED FINGER OVER FINGER
RECOMMENDED SPLICE	275 F 25 LBS 1 ---
PRESS TEMPERATURE	
PRESS PRESSURE	
ALLIGATOR LACE	
CLIPPER LACE	
GATOR LACE	OT, UCM36SP

