



BELT SPECIFICATION
CONVEYOR BELTS

FPS20-84 AI (90 DUROMETER TOP COVER W/ FRAYLESS FABRIC)

FABRIC	POLYESTER
FILL	FLEXIBLE - FRAYLESS
TOP COVER	BLUE POLYOLIFIN
TOP COVER THICKNESS	.020"
BOTTOM COVER	SATIN MAT FINISH
BOTTOM COVER THICKNESS	.020"
TOTAL BELT THICKNESS	.008"
WEIGHT PER SQ. FT.	.49
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	YES
MAXIMUM WIDTH	78-3/4"
WORKING STRENGTH @ 1% ELONGATION	57.1 LBS/INCH (10 N)
WORKING TEMPERATURE RANGE	-58 F TO 158 F
MINIMUM PULLEY DIAMETER	.98"
CO EFFICIENT OF FRICTION	.4
STEEL	
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
VULCANIZER TEMPERATURE	300 F
VULCANIZER PRESSURE	30 LBS
ALLIGATOR LACE	7
CLIPPER LACE	UX-1SP
GATOR LACE	OT, 30 LP

MEETS AND/OR EXCEEDS REQUIREMENTS FOR DIRECT CONTACT WITH TOBACCO

