



BELT SPECIFICATION
CONVEYOR BELTS

UM 22-84FF (86 DUROMETER BLUE PU, FRAYLESS FABRIC)

FABRIC	FRAYLESS POLYESTER
FILL	RIGID
NUMBER OF PILES	2
TOP COVER	BLUE PU, MATTE
TOP COVER THICKNESS	.008"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.059"
WEIGHT PER SQ. FT.	.39 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	YES
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	57.1 LBS/INCH
TEMPERATURE RANGE	-5 F TO 212 F
MINIMUM PULLEY DIAMETER	.79"
CO EFFICIENT OF FRICTION	
STEEL	.25
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER SPLICE
ALLIGATOR LACE	00
CLIPPER LACE	----
GATOR LACE	25 LL
VULCANIZER TEMPERATURE	172C
BELT TEMPERATURE	164C
VULCANIZER PRESSURE	30-35 LBS
	FOIL ON TOP

