



DERCOUSA

BELT SPECIFICATION
CONVEYOR BELTS

FABREEKA TYPE: 27-83/6 (#6 SAWTOOTH PROFILE TOP/NEGATIVE DIAMOND BOTTOM)

DERCO TYPE: 2EMA 16CST 8R N55

FABRIC	POLYESTER
FILL	RIGID
TOP COVER	BLUE PVC
PROFILE	# 6
TOP COVER THICKNESS	.063" 55 durometer
BOTTOM COVER	BLUE PVC
PROFILE	#1 DIAMOND
BOTTOM COVER THICKNESS	.6" 85 durometer
TOTAL BELT THICKNESS	.18"
WEIGHT PER SQ. FT.	..81 LBS
FOOD QUALITY	FDA
ANTI STATIC	NO
TENSILE FORCE @ 1% ELONGATION	97 LBS/INCH / 17 N/MM
WORKING TEMPERATURE RANGE	-10 F TO 230 F
MINIMUM PULLEY DIAMETER	.98"
CO EFFICIENT OF FRICTION	
STEEL	.35
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER
ALLIGATOR LACE	7, 15, 125
CLIPPER LACE	UCM36
GATOR LACE	OT, 1LP
VULCANIZER TEMPERATURE	176 C
BELT TEMPERATURE	168 C
VULCANIZER PRESSURE	30 LBS

