



BELT SPECIFICATION
CONVEYOR BELTS

12 PV (WHITE FELT TOP)

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	2
TOP COVER	WHITE POLY FELT
TOP COVER THICKNESS	
BOTTOM COVER	FABRIC-PVC IMPREGNATION
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.106"
WEIGHT PER SQ. FT.	.33 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	80"
WORKING STRENGTH @ 1% ELONGATION	34.3 LBS/INCH-6N/MM
TEMPERATURE RANGE	14 F TO 230 F
MINIMUM PULLEY DIAMETER	1.57"
CO EFFICIENT OF FRICTION	
STEEL	.2
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER SPLICE
PRESS TEMPERATURE	172 C
BELT TEMPERATURE	164 C
	PU FOIL ON BOTTOM
PRESS PRESSURE	30-35 LBS
ALLIGATOR LACE	00
CLIPPER LACE	-----
GATOR LACE	UCM36SP

